

PRODUCT SPECIFICATIONS

PRODUCT NAME:	GenieMat FAS4
DESCRIPTION:	GenieMat FAS4 wet set / semi wet set adhesive. It is solvent-free, non-flammable, has low-odour, demonstrates water resistant benefits of a hard-set adhesive, features long working time, is very quick to use and easy to trowel. This specially formulated adhesive has plasticiser migration resistance that allows installation of a broad variety of vinyl floor products.
APPLICATION:	GenieMat FAS4 is used for bonding GenieMat sound control underlayments to various subfloors/substrates, and for bonding all specified finish floors and coverings, including vinyl floor products, to GenieMat sound control underlayments.
APPEARANCE:	Smooth, medium viscosity, easy to trowel, cream.
INSTALLATION METHOD:	For non porous surface allow the adhesive to tack off. Wet set application for porous surfaces: allow flash time of 5-20 minutes depending on temperature and humidity.
WORKING TIME:	10 - 30 minutes, depending on temperature and humidity
SHELF LIFE:	1 year in unopened container at 21°C

PRODUCT SPECIFICATION CONTINUED

TROWEL SELECTION AND COVERAGE:

Coverage is approximate and may vary depending on porosity of substrate and angle at which the trowel is held. It is the installer's responsibility to apply the proper amount of adhesive for the job condition.

Installation:

Trowel Size* & Notch:

Coverage:

GenieMat to porous substrate:

A2 Notch Trowel

41 - 47 m²

GenieMat to non-porous substrate:

A1 / A2 Notch Trowel

41 - 54 m²

Vinyl tile and plank to **GenieMat**:

A2 Notch Trowel for structured backings / A1 Notch Trowel for smooth backings

41 - 47 m²
47 - 54 m²

Solid vinyl sheet to

A1 / A5 Notch Trowel

47 - 61 m²

QUANTITY:

Bucket: 14 kg

TECHNICAL DATA

SUBSTRATE RELATIVE HUMIDITY TEST (BS8203):

75 % RH

APPLICATION TEMPERATURE:

Best applied between 18 - 25°C, with the floor temperature above 15°C

APPLICATION RELATIVE HUMIDITY:

Best applied relative air humidity below 65%

FREEZE/THAW STABILITY:

Stable to -14°C

AROUND THE WORLD.

PLITEQ INC.

131 Royal Group Crescent
Vaughan, ON
L4H 1X9 Canada

4211, Yonge Street,
Suite 404, Toronto, ON M2P
2A9 Canada

2015 Main St,
Vancouver, BC
V5T 3C2 Canada

T.+1 416 449 0049
info@pliteq.com
www.pliteq.com

PLITEQ (DE)

251 Little Falls Drive
Wilmington, DE
19808
United States of America

PLITEQ (AZ)

11701 N. 132nd Drive
Surprise, AZ
85379
United States of America

T.+1 480 805 5560
info@pliteq.com
www.pliteq.com

PLITEQ MEXICO

Calz. Gral. Mariano Escobedo
476-piso 12 Chapultepec
Morales, Anzures,
Miguel Hidalgo, 11590
Ciudad de México, CDMX
Mexico

T.+52 1 938 164 1551

PLITEQ (UK) LTD.

Office 205, Orega High
Holborn, 16 High Holborn,
London, WC1V 6BX
United Kingdom

T.+44 203 9846444
info@pliteq.co.uk
www.pliteq.co.uk

PLITEQ BUILDING MATERIALS TRADING LLC.

European Business Centre
Dubai Investment Park
PO Box 473 512
United Arab Emirates

T. +971 4 567 4944
info@pliteq.ae
www.pliteq.ae

PLITEQ ASIA PACIFIC PTE LTD.

#19-13, 101 Cecil Street,
Tong Eng Building, 069533
Singapore

T.+65 6813 2017
info@pliteq.sg
www.pliteq.sg

PLITEQ AUSTRALIA PTY LTD.

72 York Street, South
Melbourne, VIC, 3205
Australia

T.+61 3 9018 7696
info@pliteq.com.au
www.pliteq.com.au

